PNEUMATIC NEWS 2019



AIR POWER CONTROL

A.P.I. is an Italian company specialised in the manufacturing of **industrial pneumatic components**. Since our **birth in 1987**, we have created a company with **an international printing** and gained an increasingly important role in the market.

Innovation, design and technology of our products ensure to customers not just a product, but a sector's excellence.

We provide solutions to specific needs and offer customized products tailored to each application sector.







Micro-cylinders ISO 6432

Suitable for general applications

- Bores from 8 to 25 mm.
- Single and double acting, magnetic or not magnetic
- With or without cushions
- Hard anodized aluminium end caps
- Metallic piston with elastic damper integrated



S.S. AISI 316tube

Product Improvement



Replaceable PU seal









M seals

Low temperaturi seals



Round cylinders

An effective alternative for your applications



- Rores from 32 to 63 mm.
- Heads and tube connected by rolling
- Single or double acting, magnetic or not magnetic
 - With or without cushions











Stainless Steel Round cylinders

Suitable for Food and Chemical applications

- Bores from 32 to 63 mm.
- Heads and tube connected by rolling
- Double acting, magnetic or not magnetic
- With or without cushions



Already **Available!**



PU seals standard

OPTIONS:





ATEX compliance



Stainless Steel Round cylinders

Clean design for food applications



- Bores from 32 to 63 mm.
- Double acting, magnetic, with adjustable cushions
- Demountable nose for easy rod seal replacement
 - Replaceable seals including cushion o-rings
 - ISO 15552 with mountings



OPTIONS:







v temperatı seals

rature FKM seals ATEX compliance

Cylinders ISO 15552

Clean design

- Bores from 32 to 125 mm.
- Full metal parts
- PU seals as standard
- Replaceable seals including cushion o-rings
- Standard magnetic aluminium piston



Flat heads





BMA type profile barrel with "T" and "C" grooves



BMT type profile round tube tie rods

Already **Available!**

OPTIONS:







als

Low temperature seals



Compact cylinders ISO 21287

New look, improved performances



Stainless Steel compact cylinders ISO 21287

Suitable for Food and Chemical applications

- Bores from 25 to 100 mm.
- Double acting, magnetic
- One or more magnetic switches applicables
- Anti-rotating types available



S.S. AISI 316L





Already **Available!**

OPTIONS:







PU seals standard






Mirror polished surfaces



Magnetic switches ASH

For high temperatures



Brackets series **AS** for mounting on **ISO 15552** and **CNOMO** cylinders

Rotary actuators

Range enriched, improved performances

- Bores from 32 to 400 mm.
- Single or Double Acting
- With rack and pinion
- 1/8"G and 1/4"G air inlet
- Connections conforming to ISO 5211 (DIN 3337) and NAMUR



Hard anodized body









ATEX compliance FKM seal







VSO series with **brass** ball valve




VSI series with **stainless steel** ball valve



Solenoid valves 22 mm.


Small dimensions, great versatility



Direct mounting to the application



- 1/8" or 1/4" connections available
 - 3/2 normally closed function
 - Directly operated
 - 1/8" air inlet
 - Bistable manual override







OPTIONS:



Low temperature ATEX compliance seals

Aluminium solenoid valves

Suitable for ATEX zone

- 1/4", electrically operated
- Spring Return and Solenoid/Solenoid versions
- 3/2, 5/2 and 5/3 functions available
- Die-cast painted aluminium body
- Standard ATEX compliance



NAMUR interface

















Range **Extension**













Suitable for ATEX zone



S.S. AISI 316L



• 1/4", electrically operated

- Spring Return and Solenoid/Solenoid versions
 - 3/2, 5/2 and 5/3 functions available
 - IN-LINE or NAMUR interface available
 - Standard ATEX compliance







Range **Extension**



Stainless Steel air-line equipment

Suitable for Food and Chemical applications

- 1/4", 1/2" and 1"
- Working pressure up to 60 bar
- Standard NACE compliance
- Supplied complete with stainless steel pressure-gauge and bracket



S.S. AISI 316L











Range **Extension**

OPTIONS:





Low temperature seals



Mountings for cylinders

ISO mountings range enriched

- From Ø 12 to 320 mm.
- Aluminium mountings for ISO 15552 cylinders and ISO 21287 compact cylinders
 - Steel mountings for ISO 15552 cylinders and ISO 21287 compact cylinders
- Stainless steel mountings for ISO 15552 cylinders and ISO 21287 compact cylinders
 - Complete with screws or screws and pin













MANY FIELDS

ONE TARGET ONLY



food and beverage



automation



plastics



depuration



packaging



glass



medical



electronic components



wood



energy production



ceramics



textile



graphics



chemical



cleaning







QUALITY



INNOVATION



DESIGN



TECHNOLOGY



SYNERGY



SIMPLIFICATION







A.P.I. S.r.I.

Via Cornaggia, 107 - 22076 Mozzate (CO) - Italy Tel. +39 0331.82.35.11 - Fax +39 0331.82.34.80 info@api-pneumatic.com

api-pneumatic.com