

Foot operated valves 1/4"

1/4", 3/2 and 5/2 foot single and two stable position



Standard executions			
Version	Symbol	Code	Item
3/2, normally closed, 1 position with safety device		033127	AVP230
3/2 normally closed, 2 positions with safety device		033128	AVP232
5/2, 1 position with safety device		033129	AVP250
5/2, 2 positions with safety device		033133	AVP251



Series of pedals with 3/2 or 5/2 valve, single and two stable position. In the standard version they are provided with 1/4" spool valve and yellow shock-resistant protection in acetal resin and safety device to avoid possible improper actuations.



Type: **AVP2...**

Technical data											
Fluid	Compressed filtered air with or without lubrication. Lubrication, if started, must be continued.										
Pressure range	2,5 ÷ 10 bar										
Temperature range	0 °C ÷ + 50 °C										
Orifice	6,5 mm										
Flow	1000 NI/min										
Operating force	50 N										
Materials	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">Housing:</td> <td>Shock-resistant acetal resin</td> </tr> <tr> <td>Valve body:</td> <td>Profiled anodised aluminium</td> </tr> <tr> <td>Valve internal parts:</td> <td>Nickel plated brass/Nickel plated aluminium/Stainless steel</td> </tr> <tr> <td>Seals:</td> <td>NBR</td> </tr> <tr> <td>Protection cover:</td> <td>Shock-resistant acetal resin</td> </tr> </table>	Housing:	Shock-resistant acetal resin	Valve body:	Profiled anodised aluminium	Valve internal parts:	Nickel plated brass/Nickel plated aluminium/Stainless steel	Seals:	NBR	Protection cover:	Shock-resistant acetal resin
Housing:	Shock-resistant acetal resin										
Valve body:	Profiled anodised aluminium										
Valve internal parts:	Nickel plated brass/Nickel plated aluminium/Stainless steel										
Seals:	NBR										
Protection cover:	Shock-resistant acetal resin										